321/321H
UNS S32100/S32109

jjmfg.com | sales@jjmfg.com | (800) 231-4253

DESCRIPTION

Stainless 321 is a heat resistant, titanium stabilized, austenitic alloy that is commonly used for service in the 1000°F-1600°F temperature range. Stainless 321 is primarily used in applications that involve continuous and intermittent service temperatures within the carbide precipitation range of 800°F-1500°F.

LIMITING CHEMICAL COMPOSITION (%)

C	CR	MN	NI	P	S	SI	TI
MAX 0.08	17.0-20.0	MAX 2.0	9.0-13.0	MAX 0.04	MAX 0.03	MAX 0.75	Trace*

*The titanium content shall not be less than 5 times the carbon content and not more than 0.60%. Note: 321H requires the titanium content to be not less than 4 times the carbon content and not more than 0.60%.

TYPICAL APPLICATIONS

- High temperature chemical processes
- Heat exchanger tubes
- Refineries
- High temperature steam service

TENSILE REQUIREMENTS

TENSILE STRENGTH (KSI)	YIELD STRENGTH (KSI)
75	30

PRODUCT CAPABILITIES

J&J Alloys produces a wide selection of fittings, flanges, and custom components tailored to customer specifications and technical drawings. For custom inquiries or additional details, please contact your J&J Alloys sales representative.

PRODUCT	SIZE (NPS)	PRODUCT	SIZE (NPS)	PRODUCT	SIZE (NPS)
SW/THRD Couplings	1/8” - 8”	SW/THRD 90s	1/2” - 4”	BW Tees	1/2” - 10”
SW/THRD Half Couplings	1/8” - 8”	SW/THRD 90s (Block Pattern)	1/2” - 4”	BW LR/SR 90s (Block Pattern)	1/2” - 4”
THRD Plugs (Hex/Round/Square)	1/8” - 6”	SW/THRD Tees	1/2” - 4”	BW Cross (Block Pattern)	1/2” - 12”
THRD Hex Bushings	1/8” - 6”	SW/THRD Cross (Block Pattern)	1/2” - 4”	Pipe Nipples	1/4” - 8”
SW/THRD Inserts	1/8” - 4”	SW/THRD Caps	1/2” - 6”	Studding Outlets (Flat Bottom)	1/2” - 24”
BW/SW/THRD Unions	1/8” - 4”	BW Caps (Dome Shaped)	1/2” - 24”	ASME B16.5 (dims) Flanges	1/2” - 24”
Olets (TOL, SOL, WOL, EOL, LOL)	1/8” - 24”	MSS (Short) Stub Ends	1/2” - 60”	ASME B16.47 Flanges Series A&B	26” - 60”
Conc/Ecc Swages	1/2” - 8”	ASA (Long) Stub Ends	1/2” - 60”	Taper Bore BW 45s	1/2” - 30”
SW/THRD 45s	1/2” - 4”	BW Concentric Reducers	3/4” - 30”	Taper Bore BW 90s	1/2” - 30”
SW/THRD 45s (Block Pattern)	1/2” - 4”	BW Eccentric Reducers	3/4” - 24”	Taper Bore BW Tees	1/2” - 30”

NOTE: The information on this sheet have been compiled from a variety of sources, and should be considered as a general guide only. The information and data included are accurate to the best of our knowledge, and may be revised at any time without notice. J&J Alloys assumes no responsibility for the accuracy of this information.

REV 10-29-26